



Combined Materials

- Stationary Ring(Carbon/SiC)
- Rotary Ring (Ceramic/SiC)
- Secondary Seal (NBR/EPDM/Viton)
- Spring and Punched Parts (Steel)

Working Conditions

- Mediums: Water, oil, and weakly-corrosive mediums, etc.
- Temperature: -20°C~100°C
- Pressure: $\leq 0.3\text{MPa}$
- Speed: $\leq 10\text{ m/Sec}$

KY BT-A2

Compatibility:

- Burgmann BT-A2, John Crane TYPE 6A, VULCAN TYPE 75, Pac-Seal TYPE 68, Trisun TSF



Part#	d	D	D1	D2	L1	L2	L3
KY BT-A2-10	10	29	24	23	7	6	4
KY BT-A2-12	12	32	28.55	25	8	5.2	5
KY BT-A2-12A	12	35	30	24	8	5	5
KY BT-A2-12B	12	38.5	33.4	25	6	7	5
KY BT-A2-16	16	41.5	36.45	31	8	6.8	5
KY BT-A2-16	16	41.5	38.1	31	8	6.8	5
KY BT-A2-20	20	43.8	40	35	9.5	6	5
KY BT-A2-25	25	51	46/47	44	10	8	7
KY BT-A2-28	28	57	52	45	10.5	8	7.5
KY BT-A2-30	30	57	52	48	11	8	8
KY BT-A2-1/2"	12.7	35	30	25.4	8	5	6.35
KY BT-A2-5/8"	15.875	41.5	36.45	31.75	8	6.7	10.3
KY BT-A2-3/4"	19.05	43.8	40	34.925	9.5	6	10.3
KY BT-A2-1"	25.4	51	47	41.275	10	7.9	11.1

Automotive Pump Seals

▪ Add: A1001, Hebang Building, No.933 Tiantong North Road, Ningbo, China 315100

▪ Tel: +86-134-56162828

▪ Fax: +86-574-89069223

▪ Email: sales@kyltd.com